



UNIFLEX cleaning machines effectively remove residue and scale from hose cutting, crimping and press fitting.




RG 10



RG 2

We reserve the right to make technical changes without notice. Options are machine parts that can only be ordered while buying the machine.

Accessories



UNIFLEX cleaning machines effectively remove residue and scale from hose cutting, crimping and press fitting.



Flushing cone



Suction filter

Pressure filter
600.901 5 µm



RG 2



RG 10

Technical data	RG 2	RG 10
Drive	Diaphragm pump, 7 bar Air	Diaphragm pump, 7 bar Air
Maximum flow rate	25 l/min	180 l/min
Pressure filter	5 µm	10 µm
Air filter	5 µm	5 µm
Max. air consumption	100 NI/min	250 NI/min
Working range	up to 1 1/4" ID	up to 2" ID
Max. length, depending on bore size	2,5 m / 8 feet	20 m / 65 feet
Tank capacity	38 L	215 L
Working area	350 x 750	800 x 1600
Cleaning agent	Non-toxic and corrosion-free emulsion, water based.	Non-toxic and corrosion-free emulsion, water based.
L x W x H (mm)	960 x 435 x 940	2000 x 840 x 1050
Weight (empty)	55 kg	160 kg
Accessories		
Hakupur 10 L - RG 2+RG 10 - concentrated cleaning agent		
PJ_30.10.76 - RG 10 - Filter cartridge 5 µm		
PJ_30.10.60 - RG 10 - Filter cartridge 10 µm		
600.4 - RG 2 - Filter cartridge 5 µm		
600.5 - RG 2 - Filter cartridge 12 µm		